



# EFFECTIVE AND ENVIRONMENTALLY FRIENDLY SPREADING TECHNOLOGY

**Dribble bar systems and trailing shoe systems  
for efficient slurry management**

**VOGELSANG – LEADING IN TECHNOLOGY**

**VOGELSANG**











# You can rely on it

**Quality, experience and expertise  
guarantee future-proof technology**

**As a pioneer in agricultural technology, Vogelsang remains one of the leading mechanical engineering companies in this sector. Farmers and contractors worldwide rely on the innovative design and high quality standards of our spreading technology.**

Based on our diverse experience and continuous development work, we build highly functional components and entire systems that facilitate precise distribution of the nutrients in the slurry.

Both the production and material quality of our dribble bar systems and precision distributors are testimony to our responsible actions for the benefit of our customers. Their adaptability and versatility boost yields as well as fostering sustainability and allowing agricultural operations to react effectively to current legal requirements.



# Our invention, your benefit

## The nutrient-efficient low-level spreading system with dribble bar and trailing shoe systems

### **Slurry as a nutrient source**

Slurry and digestates are valuable reusable materials. These highly valuable nutrient sources, which contain trace elements and organic forming matter, become more important as the cost of mineral fertilizer rises. However, to use slurry as a natural source of nutrients economically, successfully and properly, the distribution system must be precise, clean and low in odors. All Vogelsang spreading systems for slurry satisfy these requirements even under difficult conditions.

### **Cutting-edge technology and superior quality**

We continuously develop and optimize our spreading technology. The practical results reveal that these efforts pay off, which has also been confirmed in various tests: Intelligent designs maximize the working widths and ensure even fertilization regardless of the weather conditions. Robust frame designs, variable management of partial width sections, optimized hose laying, innovative special solutions and precise and robust precision distributors have been ensuring the success of farms, contractors and machinery syndicates for more than 30 years.

### **Efficient and flexible spreading**

We support highly effective transport chains and umbilical application systems with linkages up to 36 m long, and up to 18 m long for self-propelled vehicles. Every system allows you to spread slurry with low emissions and efficient nutrient use. The Vogelsang range consists of conventional dribble bar systems for direct spreading in growing crops and trailing shoe systems that separate the crops and thus place the slurry under the plants.

### **Practical, rugged and convenient**

Vogelsang dribble bar systems and trailing shoe systems are tailored for the different applications of farmers, machinery syndicates and contractors. The functionality and efficiency of the systems are utilized optimally by our proven precision distributors, as they guarantee even and constant distribution of the slurry into the spreading hoses. Our linkage technology also ensures maximum precision and flexibility, offering maximum working widths with compact transport dimensions.







## Overview of Vogelsang spreading technology

### Dribble bar systems for tankers

---



#### SwingUp

- Working widths from 7.5 to 18 meters



#### SwingMax

- Working widths from 21 to 30 meters



#### SwingMax36

- Working width 36 meters

### Dribble bar systems for self-propelled vehicles

---



#### Compax

- Working widths from 12 to 18 meters

### Dribble bar systems for the umbilical application system

---



#### BacPac

- Available as dribble bar as well as trailing shoe system
- Working widths from 21 to 32 meters



## Trailing shoe systems for tankers

---



### Also in the portfolio: BlackBird® and UniSpread

Detailed information about the Vogelsang trailing shoe systems BlackBird and UniSpread can be found in the separate product brochures.

**By the way, you can find them at [vogelsang.info](http://vogelsang.info) as a download.**

## SwingMax Slide

- Working widths from 21 to 30 meters


## Precision distributors

---




### DosiMax DMX

- Maximum precision
- Variable spreading capacity
- High distribution accuracy regardless of the spreading capacity
- Easy maintenance



### ExaCut ECL

- Best cutting and distribution effect
- With heavy material separator
- Very smooth running



### ExaCut ECQ

- Fast, simple and straightforward maintenance
- Longer service life
- Better distribution precision due to flow optimization
- Low power requirements
- Large cross-sections for less pressure loss
- Resistant to dry running

### ExaCut ECC

- Innovative rotor concept without air suction
- Excellent distribution accuracy
- Tried-and-tested cutting principle
- ExaCut maintenance concept: easy und quick

# Technology with an expertise advantage

**Perfectly coordinated individual  
components for maximum functionality**

## **Spreading technology involves teamwork**

The frame, distributor, drain hoses and technical innovations – all are needed for the best spreading performance.

## **Optimum hose routing**

The discharge hoses of Vogelsang dribble bar systems all have similar lengths thanks to optimized hose guidance. The slurry reaches the soil almost simultaneously. Even spreading across the entire working width and length is ensured as well.

## **Vogelsang special hose**

Our hose material and the composition of the plastic were developed specially for Vogelsang over decades. The combination of raw materials that we use for our special hose is characterized by high robustness, elasticity and UV resistance. That makes the hoses resistant to the effects of chemicals and environmental influences. The unique manufacturing technique we use for our rigid end hoses brings additional benefits. The hose sections used as end hoses are always straight and absolutely dimensionally stable.

Your advantage is that there is no need for springs, which are prone to wear, and the hoses always remain open and do not stick. Furthermore, this rigid arrangement of the end hoses ensures a defined distance between discharge lines.

## **Vogelsang precision distributors**

Slurry, a valuable commodity, must be spread evenly and reliably in the distribution hoses. The Vogelsang precision distributor permits the precise distribution of the nutrients with a distribution coefficient of less than 5 percent. That makes spreading a safe and reliable process without fluctuations, which also guarantees the even growth of the plants.



### Section management

Retracting or folding linkage parts using TeleShift or TopSwing further reduces the transport dimensions, preventing the system from overlapping out at the front and rear of the vehicle. The patented Comfort Flow Control (CFC) system allows the corresponding discharge hose to be simply pneumatically sealed.

### DropStop



When driving on the road, the hoses of the dribble bar system are rotated upward 180° so that they are vertical. This reliably prevents leakage and keeps the road clean and safe.

### Slope compensation

Flexible drain hoses, the elastic suspension and slope compensation of the supporting frame of the SwingMax systems allow the linkage to be optimally adapted to any terrain. All rigid elements are kept at a maximum distance from the ground, making it safe to drive over uneven terrain.

### EasyPack


We supply dribble bar systems as EasyPack, completely preinstalled and tested. This makes it easy for you to quickly modify your Vogelsang dribble bar system on the farm. The system can also be installed directly on your vehicle in our factory.



# The heart of every distribution system

Precision distributors for precise and reliable nutrient distribution

## The DosiMat DMX




### Variable spreading capacity, precise distribution

With this hydraulically operated cutting and dosing system, the slurry flows from above into the distributor where it is distributed evenly to the outlets by the rotor. Fibrous matter and foreign objects are shredded reliably by the cutting blades.

What is also impressive about the DosiMat DMX is its flow-optimized rotor, which ensures outstanding distribution accuracy. It distributes large, but also small spreading capacities without the need for conversion. Its maintainability proves to be just as practical.

## The ExaCut ECL




### Optimal cutting results, maximum reliability

Thanks to its rotor technology, the compact ExaCut ECL cuts and distributes excellently. The steady rotor movements make for very smooth running. The slurry is distributed evenly to the 20 to 48 outlets.

With hose diameters up to 60 DN, even large amounts of slurry can be dealt with. With the self-adjusting and self-sharpening cutting system, the product boasts an extremely long lifetime together with maximum ease of maintenance. The integrated heavy material separator protects the entire spreading system against foreign matter.




## The ExaCut ECQ



### Expect the best

The ExaCut ECQ, a further development of the ECL, also works using rotor technology. It also has new features that put it in the top spot in the market: Unbeatable distribution accuracy and maintainability accompanied by an increase in service life and lower power requirements.

## The ExaCut ECC



### Runs easily without air

Vogelsang has now succeeded in becoming the first agricultural technology developer in the world to design a precision distributor that does not require air suction. The new ExaCut ECC has an innovative rotor concept, which prevents the formation of negative pressure. Extremely even feeding of the slurry into the hose outlets ensures an even smoother distribution process. Generous cross sections contribute to the superior smooth running of the new ExaCut ECC. The fact that these improvements actually serve to reduce power and oil requirements is certainly a welcome side effect.


# Spreading slurry precisely and cleanly

The equipment options for optimal partial width management and safe driving

**High weather resistance**  
thanks to the EPDM rubber used

**Fast opening and closing**  
through a larger air duct

**CFC deactivated:**  
Free flow without edges on which fibrous matter could accumulate



**CFC activated:**  
The outlet is securely closed

**Optimized bending behavior**  
prevents constriction during flexing

**Very simple assembly**



### Comfort Flow Control

Comfort Flow Control (CFC) is the universal solution for part-width section cutoffs, tramline switching and/or closing off selected hose groups on the dribble bar system. The patented CFC is unique in its simple and ingenious functional principle: an air bellows developed specially by Vogelsang is filled with air pressure, sealing off the slurry inflow to the corresponding discharge hose. For this purpose, the CFC is installed in the hose outlets of the spreader device immediately downstream of the respective distributor. From the cab, each hose or group of hoses can be turned off. In addition, the CFC can be used for a compact and reliable DropStop for cultivators or injectors.

### DoubleFold

DoubleFold allows you to reduce the working width. The outermost frame elements – the TopSwing – is manually folded in half. The Comfort Flow Control seals the corresponding discharge hoses.

### TopSwing

TopSwing customizes the working width by hydraulically folding the outer frame elements through 180°. The frame elements are then placed on top of the basic linkage. The corresponding discharge hoses are sealed by Comfort Flow Control.

### TeleShift


TeleShift not only reduces the transport dimensions, it also reduces the working width. The extending and retracting ends of the booms allow flexible working widths in conjunction with Comfort Flow Control.

By the way, in SwingMax linkages, the TopSwing folding mechanism can be combined with TeleShift, reducing the transport length by up to 4 meters. In this way, SwingMax linkages can also be used on compact and short tanks.


### Half-boom section switch-off

In this option, one of the two supply lines to the ExaCut is sealed pneumatically, hydraulically or manually, so that only one boom is fed with slurry.


### Standard with tramline




### DoubleFold



### TopSwing



### TeleShift



### Half-boom section switch-off





# Easy setup, powerful performance

The SwingUp with compact dimensions  
and high-grade technology for universal  
and flexible use





SwingUp is our all-rounder for slurry spreading. The dribble bar system also combines great stability and flexibility. Weighing just one metric ton and with a working width of 12 meters, SwingUp is unusually light and therefore also suitable for compact vehicles.

SwingUp means maximum spreading accuracy. This is provided by the precision distributors, Vogelsang's special hoses that adapt to the shape of the ground, and the rigid end hoses that precisely deposit the slurry on the ground and not on the plants.

This system is particularly easy to install and can be easily and quickly retrofitted on existing tankers. In general, the onboard hydraulic system of the tractor will be sufficient to control all of the functions of the dribble bar system.

Just ask and we will be glad to configure a SwingUp system for you.

### SwingUp-Features

- Highly precise distribution with the precision distributor and the double symmetrical hoses
- DropStop – by rotating the end hoses up 180°
- Transport position above the fender
- Narrow transport width
- Remote unlocking of booms
- Fixed installation on tank
- Easy to install thanks to EasyPack
- Variable mounting brackets for customized installation
- Even spraying distance between discharge hoses ensures optimum growth

### SwingUp options

- Comfort Flow Control (CFC) for part section switch-off
- Half-boom part section switch-off
- End hoses in 50 DN
- Hydraulic unlocking of the booms
- Available as 4-point design
- TeleShift at rear/front to reduce the transport dimensions
- Complete installation on tanker at the Vogelsang factory

### Working widths

- 7.5 | 9 | 12 | 15 | 18 m
- Custom widths available upon request



### What our customers say

*"With the SwingUp system including part section switch-off we are able to meet the exacting demands of our customers. Whatever the crops and weather, the spreading is perfect with minimum odor. This is a fact for which both the farmers and their neighbors are thankful."*

Christof Schürmann, agricultural contractor, Börger, Germany




# Compact, versatile and easy to install

## The SwingUp

### Accurate precision distributors

Maximum reliability, precise distribution of nutrients and optimal shredding of foreign and fibrous matter for minimized downtime



### Special hose

Robustness, elasticity, and UV resistance thanks to unique production process

## MAXIMUM SPREADING ACCURACY


Optimal use of nutrients thanks to precise application under the crops

### Clever hose routing

Discharge hoses of approximately the same lengths to prevent the "V shape" that can form at the start

### Rigid end hoses

Even spraying distance, no overlapping of hoses as well as precise spreading of slurry under the crops for minimized crop contamination



### TeleShift

Allows the boom ends to extend or retract for transport purposes or in order to reduce the working width

### Sturdy, fully galvanized frame designs

Durability coupled with low overall weight



# Maximum performance and flexibility

The versatile SwingMax  
for maximum effectiveness



SwingMax is the optimum solution for slurry spreading with large working widths. Optional features like TopSwing, DoubleFold, TeleShift and Comfort Flow Control ensure maximum flexibility in use. The special double-frame design is able to deal with maximum dynamic loads, thereby ensuring trouble-free, cost-effective operation with weight optimization at the same time.

The coordinated hydraulic and mechanical components in the SwingMax ensure secure and speedy folding and unfolding. At the heart of the SwingMax are the ExaCut distributors located decentralized in the booms, which can be configured according to the customer's specifications. The location of the precision distributors ensures quick-and-easy access at any time for maintenance work.

SwingMax provides professional technology for the most stringent requirements, suitable for agricultural contractors, machinery rings and large agricultural operations. It offers profitability through maximum efficiency.

### SwingMax-Features

- Boom with double tubular frame for extra stability
- Maximum spreading accuracy thanks to ExaCut distributor and double symmetrical hoses
- DropStop – by rotating the end hoses up 180°
- Transport position above the fender
- Slope compensation, passive via central suspension
- TopSwing to reduce the transport dimensions
- Mounted in a 4-point design
- Compact installation on the tanker
- Easy to install thanks to EasyPack
- Even spraying distance between discharge hoses ensures optimum growth

### SwingMax options

- Comfort Flow Control (CFC) for part section switch-off
- Half-boom part section switch-off
- End hoses in 50 DN
- DoubleFold
- TeleShift at rear/front to reduce the transport dimensions
- Active slope compensation

### Working widths

- 21 | 24 | 27 | 28 | 30 m
- Custom widths available upon request



### What our customers say

*"As a contracting company, we work with very different media. Thin and thick slurry is no problem for Vogelsang's SwingMax and meets our requirements. In addition to good value for money we also record a low ratio wear and tear. Because of this and the high reliability of the SwingMax, we can work profitably, efficiently and reliably."*

Alexander Hackstedt, agricultural contractor, Höltinghausen




# Flexible, powerful and effective

## The SwingMax

### Comfort Flow Control (CFC)

Allows individually defined hose groups to be switched off using air pressure. This is controlled from the driver's cab



### Special hose

Robustness, elasticity, and UV resistance thanks to a unique production process

### Accurate precision distributors

Maximum reliability, precise distribution of nutrients and optimal shredding of foreign and fibrous matter for minimized downtime

### Clever hose routing

Discharge hoses of approximately the same lengths to prevent the "V shape" that can form at the start

### MAXIMUM SPREADING ACCURACY

Optimal use of nutrients thanks to precise application under the crops

### High effectiveness

Optimum working width for minimal costs, time savings and less travel

### Sturdy, fully galvanized frame designs

Durability coupled with low overall weight

### Compact transport widths

Minimal transport widths with optimal working widths of up to 36 meters



### Rigid end hoses

Even spraying distance, no overlapping of hoses as well as precise spreading of slurry under the crops for minimized crop contamination

### Ultimate flexibility

Flexible management of part-width sections to suit every tramline and working width



# A new dimension in dribble bar systems

The SwingMax36 with an unrivaled working width of 36 meters with great flexibility and stability





SwingMax36 advances to a new dimension. For the first time, it's now possible to spread organic fertilizer evenly across a working width of 36 meters. This allows the existing tramlines to be used, reducing the cost and time taken to a minimum, as well as the amount of travel across the field.

SwingMax36 is also designed for maximum flexibility. Intelligent section management means that the 36 meter linkage can be adjusted flexibly to working widths of 21, 24 or 30 meters. This is made possible by the TeleShift and TopSwing elements.

SwingMax36 is a design based on the tried-and-tested SwingMax3 dribble bar system. The framework has been designed as a triple construction due to the huge working width and an additional folding element was added. Three ExaCut precision distributors ensure precise spreading.



### SwingMax36 features

- Boom with double tubular frame for extra stability
- Maximum spreading accuracy thanks to ExaCut distributor and double symmetrical hoses
- DropStop – by rotating the end hoses up 180°
- Transport position above the fender
- Slope compensation, passive via central suspension
- TopSwing to reduce the transport dimensions
- Mounted in a 4-point design
- DoubleFold
- Compact installation on the tanker
- Even spraying distance between discharge hoses ensures optimum growth

### SwingMax36 options

- Comfort Flow Control (CFC) for part section switch-off
- End hoses in 50 DN
- TeleShift at rear/front to reduce the transport dimensions
- Active slope compensation



### What our customers say

*"Our customers on the island of Rügen have strict demands for the spreading technology and require a working width of 36 meters. The SwingMax system allows me to meet these requirements easily. The device is excellently finished, durable and versatile in use. Maintenance work is rarely required and completed quickly by Vogelsang's service team, so extended downtime is never a problem."*

Anton Reetz,  
Rügen Agricultural Service, Garz, Germany



# The flexible solution for self-propelled vehicles

Compax for efficient spreading and maximum efficiency with a large working width and compact transport dimensions





The Compax dribble bar system and self-propelled vehicles are an excellent combination for spreading slurry that is easy on the soil. The folding technology of the Compax was adapted for spreading slurry with a self-propelled vehicle: The Compax folds up completely behind the vehicle so that the driver's vision is not blocked and the width of the vehicle is not enlarged.

Overall, the Compax was designed to accommodate the special requirements of self-propelled vehicles that are used in season around the clock. The liquid dispersal system, hoses and ExaCut distributor are designed to spread large amounts at maximum speed.

### Compax-Features

- Maximum spreading accuracy thanks to ExaCut precision distributor
- Compact transport dimensions of 3 meters behind the self-propelled vehicle
- Electrohydraulic folding
- DropStop – by means of CFC hose switch-off
- Slope compensation, passive via central suspension
- Discharge and end hoses in 50 DN
- Mounted in a 3-point design
- Even spraying distance between discharge hoses ensures optimum growth

### Compax options

- Comfort Flow Control (CFC) for part section switch-off
- Active slope compensation

### Working widths

- 12 | 15 | 18 m



### What our customers say

*"The Compax dribble bar system is a perfect match for our self-propelled vehicles. With a transport width of 3 meters, the machine is very easy to use. Depending on the length of the field, I can adjust the working width to 9, 12 or 15 meters and thereby give my customers very economical and attractive offers."*

Rainer Fischer, Heinrich Fischer GmbH  
Contractor, Damme



# Lightweight, stable and super smart

**BackPac – The intelligent trailing shoe  
and dribble bar system for umbilical  
application systems**

Especially in larger farms or farms with rolling hills, slurry spreading via an umbilical application system has become an established method. Not only because supplying fertilizer via an umbilical application system is extremely efficient, but also the fact that there is no tanker has a positive effect on the field: The considerably lower weight of the tractor and linkage protects the soil.

Vogelsang's solution is the BackPac with a more stable linkage and a stronger pull swivel as well as with a more strategically placed precision distributor: Mounted almost centrally, it provides a corresponding center of gravity when folded. The fact that the hose lengths in the linkage could also be adjusted as a result also contributes to a more constant flow of slurry.





### New: Flow rate and pressure measurement

The pressure at which the slurry flows through the BackPac can now be read off at the driver's terminal, as it can be delivered with flow rate and pressure measurement function if required. This makes it possible to monitor the operation of the pump that fills the umbilical application system and also to record the slurry quantity applied.

### New: Integrated electrohydraulics

The BackPac linkage's electrohydraulic system can also be controlled from the terminal and is connected to the tractor via the ISOBUS.

### New: The headland management function

A further innovation in the field of slurry flow control enables the driver to stop spreading the slurry on the headland through the right or left side of the linkage at the push of a button. When the "headland management" function is activated, the slurry is either not spread at all or only spread at one side depending on the setting when turning. The function initiates the automatic closing of the part-width gate valves, switches off the entire distributor and locks the corresponding discharge hoses via the CFC.



With trailing shoe



With dribble bar

### BackPac-Features

- Mounted in a 3 point design
- Reinforced frame and pull swivel to protect against deformation
- Compatible with ExaCut ECL and ETX precision distributors for the highest distribution accuracy
- Low weight and compact design
- Optimized center of gravity for smoother driving on the field
- Transport position behind the tractor (transport width 2.55 m)
- Headland management function
- Half-boom part-width section switch-off
- Integrated electrohydraulics
- Controllable oscillation movement
- Active slope compensation from 21 m

### BackPac options

- Comfort Flow Control (CFC) for part-width section switch-off
- Digital flow rate and pressure measurement, can be called up on the terminal
- Automatic unfolding procedure
- Lifting device

### Designs

- Available as dribble bar and trailing shoe system

### Working widths

- 21 | 24 | 27 | 30 | 32\* m

\* Only with dribble bar



### What our customers say

*"When spreading slurry, we seek to maximize efficiency and minimize soil compression on our farm. That is why we chose an umbilical application system for slurry. Whether spreading slurry on crops or a meadow, the Vogelsang BackPac dribble bar system allows you to spread slurry quickly, precisely and reliably."*

Gerd Wolken, Wolken Wittmund  
Agricultural Contractor, Wittmund, Germany



# Nutrient-efficient and low emissions

**The trailing shoe system SwingMax Slide for gentle slurry spreading in growing crops**

To make optimal use of slurry, soil-level depositing of the slurry under the crops is ideal. That allows the plants to absorb the nutrients efficiently, without contaminating the crops. This process has a positive impact on the yield and creates ideal growth conditions, especially for pastureland.





The trailing shoe systems operate with an integrated skid that separates the plants and deposits the slurry in a narrow strip behind the skid. This not only prevents contamination of crops but also deposits the slurry exactly at the place the plants require it. The trailing shoe system is versatile and can be used on all kinds of crops. The trailing shoe always follows the contour of the soil thanks to its sturdy and permanently elastic shaft material. That ensures even spreading close to the soil for many years, even on uneven terrain.

As with other dribble bar systems, the weight-optimized design of this linkage permits large working widths of up to 30 meters. This means already existing tramlines can be used with less impact on the soil. This achieves a level of effectiveness never before seen in trailing shoe technology. Please note that the Vogelsang trailing shoe systems are also available as a BaseRunner retrofit kit, allowing you to convert existing dribble bar systems in just a few steps.



### SwingMax Slide-Features

- Boom with double tubular frame for extra stability
- Maximum spreading accuracy thanks to ExaCut distributor and double symmetrical hoses
- DropStop – by rotating the end hoses up 180°
- Transport position above the fender
- Slope compensation, passive via central suspension
- TopSwing to reduce the transport dimensions
- Mounted in a 4-point design
- Compact installation on the tanker
- Easy to install thanks to EasyPack
- Even spraying distance between discharge hoses ensures optimum growth

### SwingMax Slide-options

- Comfort Flow Control (CFC) for part section switch-off
- Half-boom part section switch-off
- End hoses in 50 DN
- DoubleFold
- TeleShift at rear/front to reduce the transport dimensions
- Active slope compensation

### What our customers say

*"Reliable technology is important for me. The SwingMax Slide allows me to use a wide range of working widths. The low weight was also a key point for my purchase decision. The simple operation, the low operating costs, combined with the high-quality finishing, confirmed my choice. It offers great bang for your buck!"*

Jakob Eveslage, Eveslage Contractors, Dinklage, Germany

### Also in the portfolio: BlackBird® and UniSpread

Detailed information about the Vogelsang trailing shoe systems BlackBird and UniSpread can be found in the separate product brochures.

**By the way, you can also find them at [vogelsang.info](http://vogelsang.info) as a download.**



# When it comes to service, we leave nothing to chance

**Comprehensive services for smooth operation and a long lifetime**

## **Support and supply from A to Z**

Because we are aware that close customer proximity is essential for our mutual success, we design our services to best meet your needs. In Germany and in countries where we have subsidiaries, Vogelsang service centers and contractual partners generate an active dialog with our customers and provide reliable support.

This means you always get the precise support you need in every phase of our partnership. Our highly qualified staff make it possible – experts such as consultants and technicians who know your Vogelsang machines inside and out.



Since its establishment in 1929, Vogelsang has become an internationally recognized mechanical engineering company with numerous branches, sales centers and subsidiaries.



### **We think ahead**

Thinking ahead in your best interest begins with our extensive and detailed product documentation. Spare parts are available within a short time due to our high degree of vertical integration in production. In addition, you will always find an authorized service partner in your area who can help with repairs and wear part replacement. The Vogelsang ServicePack completes the offer. Whether you need start-up, on-site training, training at the Vogelsang facility, or full service support with a maintenance contract and a wear parts service package – we offer a support program tailored specifically to your needs.



## What we offer

We provide solutions in the following sectors:  
AGRICULTURAL TECHNOLOGY, BIOGAS,  
INDUSTRY, TRANSPORTATION, WASTEWATER



## Our broad range of products and services

- Consulting and service
- Data management and control technology
- Disintegration technology
- Individually tailored solutions for special applications
- Pumps and pump systems
- Solid matter feeders
- Spreading technology
- Supply and disposal systems for railway, busses and boats
- Wet grinders and solids reduction as well as separation technology

Copyright 2025 Vogelsang GmbH & Co. KG

Product availability, appearance, technical specifications and details are subject to continuous development.

All information presented here is therefore subject to change. In selected countries, Vogelsang®, BioCut®, BlackBird®, CC-Serie®, EnergyJet®, HiCone®, PreMix®, RotaCut®, XRipper®, XSplit® and XTill® are registered trademarks of Vogelsang GmbH & Co. KG, Essen (Oldenburg), Germany. All rights reserved, including the rights to all graphics and images.

Effective and environmentally friendly spreading technology\_EN-INT\_06207725\_MET0000002 – Printed in Germany

Vogelsang GmbH & Co. KG  
Holthoege 10 – 14 | 49632 Essen (Oldenburg) | Germany  
Phone: +49 5434 83 - 0 | Fax: +49 5434 83 -10  
germany@vogelsang.info

**vogelsang.info**

